

e-STUDIO™ 2500c/3500c/3510c

Created for
BUSINESS,
focused on
COLOUR



TOSHIBA

e-STUDIO™ 2500c/3500c/3510c

SPECIFICATIONS

The Toshiba e-STUDIO2500c/3500c/3510c are powerful, multifunction colour copiers that combine the performance of a multifunction system with the quality of a professional graphics solution. Outstanding speed, performance, and professional-quality colour as well as detailed text and graphics can be yours – everyday, all the time. Thanks to Toshiba proprietary print technology, the e-STUDIO2500c/3500c/3510c devices are the ideal, cost-effective graphic/business solution for even the busiest office and pay-for-print environments.

Multifunction COLOUR



SPECIFICATIONS

Copying Process	4-Drum Electrostatic Photographic Transfer System with Internal Transfer Belt
Copying Type	4-Beam Colour Laser (8 bit)
Copy/Print Resolution	600 x 600 dpi (2400 x 600 dpi B&W equivalent)
Copy/Print Speed	e-STUDIO3510c – 35 PPM Colour / 45 PPM B&W e-STUDIO3500c – 35 PPM Colour / 35 PPM B&W e-STUDIO2500c – 25 PPM Colour / 35 PPM B&W
Warm-Up Time	Approx. 99 Seconds
First Copy Out Time	Less than 6.5 Sec. B&W (5.2 Sec. for 3510c), 8.6 Sec. Colour
Duty Cycle	e-STUDIO3510c – 70,000 Copies e-STUDIO3500c – 70,000 Copies e-STUDIO2500c – 50,000 Copies
Multiple Copying	Up to 999 Copies
Acceptable Paper Size and Weight	Cassette: ST-R to LD (17 lbs. Bond - 90 lbs. Index) Bypass: ST-R to 12" x 18" (17 lbs. Bond - 140 lbs. Index) LCF: LT (17 lbs. - 28 lbs. Bond)
Processor	Power PC 867 MHz Shared
Memory (Min/Max)	Main Memory: 512 MB / 1 GB Page Memory: 256 MB / 512 MB HD: 80 MB
Reduction/Enlargement	25% to 400%
Bypass	100-Sheet "Smart" Bypass (17 lbs. Bond - 140 lbs. Index)
Control Panel	Colour Half VGA Tilttable LCD Touch Panel
Paper Supply	Up to 3,700-Sheet Input Capacity Standard: 2 x 550-Sheet Cassettes 100 Sheet Bypass Optional: 1 x 550-Sheet PFP, 1 x 550 Sheet Cassette 1 x 2,500-Sheet LCF
Duplex	Standard Trayless Automatic Duplex Unit
Dimensions (W x D x H)	Approx. 27.5" x 30.5" x 30" (699mm x 776mm x 759mm)
Weight	Approx. 265 lbs. (120kg)
PM Cycle	50,000/70,000/70,000
Drum Type/Yield	Organic Photoconductor / 50,000/70,000/70,000
CMYK Toner Yield	CMY: 21,000 / K: 24,000
Black Developer Yield	50,000/70,000/70,000
Power Supply	115 V, 15 Amps
Power Consumption	Maximum 1.5 kW

PRINT SPECIFICATIONS

PDL Support	PCL6 & PostScript 3
Operating Systems	Netware 4.x, 5.x, 6.x, Windows Me/2000/XP, Windows NT 4.0, Windows Server 2003, Citrix MetaFrame, Macintosh, Linux, UNIX
Protocol Support	IPX/SPX, TCP/IP, EtherTalk, AppleTalk, NetBIOS Over TCP/IP LPR/LPD, IPP, SMB, SNMP, Netware, Port 9100, Bluetooth (HCRP)
Drivers	Windows Me, 2000, Server 2003, XP, NT 4.0, Macintosh OS 8.6, 9.x, 10.1/10.2/10.3, UNIX, AS400 via iData & Port 9100, SAP R/3
Connectivity	10BaseT/100BaseTX Ethernet, 802.11b/g Wireless LAN, USB, Bluetooth (HCRP)
Device Management	TopAccess
Certification	WHQL, Novell

SCAN SPECIFICATIONS

Scan Resolution	150 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan Speed	40 SPM Colour / 50 SPM B&W
File Format	TIFF, PDF, JPEG
Authentication	LDAP, SMTP

FACSIMILE SPECIFICATIONS

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approximately 3 Seconds Per Page
Fax Modem Speed	33.6 Kbps
Fax Memory	240 MB Transmission, 120 MB Reception
Memory Transmission	100 Jobs, 1,000 Destinations Max. 400 Destinations / Job
Scan Speed	.7 Seconds Per Page, 50 SPM

e-FILING SPECIFICATIONS

Operation Method	Colour Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder 200 Pages Per Document

OPTIONS

MR-3018	RADF	100 Sheets
KD-1018	Paper Feed Pedestal	550-Sheet Pedestal, Statement-R to Ledger
MY-1031	Cassette Module	550-Sheet Drawer, Statement-R to Ledger
KD-1019LT	Large Capacity Feeder (LCF)	2,500-Sheet Drawer, Letter
MJ-1101	Multi-Position Finisher	Stationary Tray: 250 Sheets (Lt) Tray 1 Stack Capacity: 2,000 Sheets (Lt) Staple Capacity: 50 Sheets (Lt/Lt-R)
MJ-1030	Saddle-Stitch Finisher	Tray 1 Stack Capacity: 1,000 Sheets (Lt) Tray 2 Stack Capacity: 1,000 Sheets (Lt) Staple Capacity: 50 Sheets (Lt/Lt-R)
MJ-6101N	Hole Punch Unit	(for MJ-1101) 2- or 3-Hole Punch Capability
MJ-6004N	Hole Punch Unit	(for MJ-1030) 2- or 3-Hole Punch Capability
KN-3500	Bridge Kit	Required with MJ-1101, MJ-1030
GA-1210	EFI Controller	
GD-1210NA	Fax Board	
GD-1160NA	2nd Line Fax	
GN-1041	Wireless LAN Adapter	
GN-2010	Bluetooth Adapter	
GN-3010	Wireless Antenna	
GP-1060	Data Overwrite Kit	
GC-1250	Main Expansion Memory	
GC-1260	Page Expansion Memory	



TOSHIBA

TOSHIBA OF CANADA LIMITED
OFFICE PRODUCTS GROUP

DIGITAL COPIERS • FAX/MFP • BUSINESS COMMUNICATION SOLUTIONS

HEAD OFFICE: 191 McNabb Street, Markham, Ontario, Canada L3R 8H2 Tel: (905) 470-3500 Fax: (905) 470-3459

WESTERN REGIONAL OFFICES: 349-25th Street, Calgary, Alberta, Canada T2A 7H8 Tel: (403) 248-3883 Fax: (403) 248-3926

13551 Commerce Parkway, Suite 110, Richmond, British Columbia, V6V 2L1 Tel: (604) 303-2500 Fax: (604) 303-2501

EASTERN REGIONAL OFFICE: 1467 Wellington Street, Montreal, Quebec, Canada H3K 1V6 Tel: (514) 527-2381 Fax: (514) 527-1381

Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates, based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.

AUTHORIZED TOSHIBA DEALER